

DESCRIPTION

ADDID® 900 is an adhesion promoter for solventborne and waterborne primers and coating formulations. It is based on an amino-functional silane.

KEY BENEFITS

promotes adhesion on metal, glass, and ceramic surfaces

SUITABILITY

waterborne	solventborne
●	●
polyurethane	alkyd resins
●	●
epoxy resins	polyester resins
●	●

● not suitable ● partly suitable ● suitable

TECHNICAL DATA

active matter content	100 %
appearance	clear liquid
chemical description	amino-functional alkoxy silane

SOLUBILITY

Water	Acetone
●	●
Butylacetate	Xylene
●	●
Butyl glycol	Styrene
●	●

● not soluble ● partly soluble ● soluble

TYPICAL APPLICATIONS

- Architectural paints
- General industrial coatings

RECOMMENDED ADDITION LEVEL

As supplied calculated on total formulation: 1.0 - 5.0 %

PROCESSING INSTRUCTIONS

Addition to waterborne or solventborne coating as supplied or as a predilution is possible.

HANDLING & STORAGE

When stored in an original unopened packaging between -40 and +40 °C, the product has a shelf life of at least 24 months from the date of manufacture. The product should be stored under the exclusion of air, light and moisture. Containers that have been opened should be blanketed with inert gas and sealed tightly.

MSDS & REGULATORY INFORMATION

This information and all further technical advice are based on our present knowledge and experience. However, it implies no liability or other legal responsibility on our part, including with regard to existing third party intellectual property rights, especially patent rights. In particular, no warranty, whether express or implied, or guarantee of product properties in the legal sense is intended or implied. We reserve the right to make any changes according to technological progress or further developments. The customer is not released from the obligation to conduct careful inspection and testing of incoming goods. Performance of the product described herein should be verified by testing, which should be carried out only by qualified experts in the sole responsibility of a customer. Reference to trade names used by other companies is neither a recommendation, nor does it imply that similar products could not be used.

Evonik Resource Efficiency GmbH | Goldschmidtstraße 100, 45127 Essen, Germany | Telefon +49 201 173-2222 Telefax +49 201 173-1939 | www.coating-additives.com